


The First 45

Standard Equipment and Options



LOA	46'2"
Hull length	44'11"
LWL	38'7"
Beam	13'9"
Displacement	23,369 lbs
Sail area	1,237 sq ft
Draft	(standard) 7'10" ..(optional) 9'
Ballast (standard)	9,876 lb
Ballast (optional)	8,543 lbs
Fuel capacity	53 gal
Water	140 gal
Auxiliary	54 hp
Hull Design: Philippe Briand	

Rig Dimensions: Mast	Classic
I	57'5"
J	17'5"
P	55'9"
E	18'

CONSTRUCTION

Hull constructed of hand-laid solid GRP bonded to a structural grid/hull liner of directional fiberglass/GRP for a strong, stiff, light composite. Vinyl ester hull barrier coat to resist osmotic blistering and zone-specific stitchmat laminates for specific increased strength optimization.

Deck constructed of Cored GRP sandwich construction for stiffness, thermal and acoustic insulation and lighter weight. Solid fiberglass reinforcements in high load areas. Integral unidirectional GRP deck beams for added strength. Main bulkheads bonded 360° to the hull and deck for rigid torsional and compression strength.

White hull, grey hull decoration

DECK EQUIPMENT

RIGGING

Standard 9/10 anodized aluminum mast and boom, keel stepped with triple spreader

(3) Folding steps on mast

Rigid boom vang led to cockpit

DYFORM discontinuous standing rigging

Single backstay w/hydraulic adjuster

Genoa furler, drum on deck

Mainsheet traveler on cockpit sole

(2) Genoa sheet tracks w/lead cars adjustable from cockpit

Complete running rigging Dyneema®: (1) genoa halyard, (1) genoa furler line, (2) Genoa sheets, (2) back and forth genoa traveller, (1) main halyard, (1) mainsail foot, (1) mainsail sheet in cockpit, (3) reef lines, (12) line clutches

(2) Deck organizer on cabin top

Deck is pre-fitted for installation of spinnaker gear

WINCHES

Aluminum Harken winches self tailing:

(1) Mainsail/spinnaker winch 44.2 STA on cockpit coaming

(2) Maneuvering winches 44.2 STA on deck house

(2) Genoa sheet winches 53.2 STA on cockpit coamings

(2) Winch handles

BOW – MOORING – ANCHORING

(1) Stainless steel bow fitting, asymmetric spinnaker securing point

Removable stainless steel stem roller

Self-bailing chain locker

Vertical electric windlass 1000 Watt w/remote control

Sail locker

(6) Aluminum mooring cleats, stainless steel chafe guards on deck

SAFETY

(1) Stainless steel bow pulpit

(2) Stainless steel stern pulpits w/dual lifeline transom gate

Double lifelines with gates and stainless steel stanchions

Flag pole holder, life ring bracket

(2) Eye pads for harness (companionway and on mainsail mounting)

COCKPIT

Self bailing cockpit w/storage compartments under sole

(2) Cockpit lockers under bench seats

(1) Propane locker, aft of steering station

(1) Life raft locker in cockpit bottom w/lid

Cockpit bench seats and helm seat w/wood inlays

Dual steering pedestals in lacquered aluminum, two stainless steering wheels, leather covered (35" diameter)

(1) Emergency tiller

Dual compasses

Engine shifter and control panel at end of starboard cockpit bench

Spaces for navigation electronics (optional extra)

recessed into port and starboard cockpit benches

SUN DECK AND STERN

Open transom w/lifelines

Stainless steel swim ladder

Cold water transom shower

ACCOMMODATIONS

Light oak colored ALPI interior woodwork

Parquet type laminated floors

COMPANIONWAY

Headroom: 6'5"

Molded wood steps with non-slip surface

(2) Stainless steel handrails

FORWARD CABIN

Headroom 6'4"

Centerline "queen" berth w/marine mattress and padded headboard

Hanging locker, (2) drawers, storage locker, dressing table, cubbyholes along the hull

(1) Opening deck hatch w/Ocean Air shade and screen

(2) Fixed hull portholes

FORWARD HEAD

Headroom: 6'4"

Separate stall shower

Manual marine toilet w/21 gal. holding tank

Countertop with square synthetic resin sink

Storage cupboard with drawer, closed locker

Toilet accessories: Paper dispenser, trash bin

(2) Mirrors

(1) Opening deck hatch w/ Ocean Air shade/screen

SALON

Headroom: 6'4"

L-shaped bench seat, double density foam

(1) Rectangular salon table

Starboard settee

Storage under seats

Stainless steel handrails under coamings

(2) Opening deck hatches w/Ocean Air shade/screen

(2) Fixed hull portholes

GALLEY TO STARBOARD

Headroom: 6'6"

T-shaped galley w/handrails

Rectangular sink w/closed drain rack

(1) 2 burner gimbaled stove w/oven

Front opening 12 Volt evaporator fridge, 3.4 cubic foot w/storage baskets

(1) Top opening Ice box, 2.1 cubic foot

Galley accessories: Cutting board, trash bin, sponge holder, stainless steel dish drain rack

Cutlery drawer, bottle holder

Leather covered stainless steel handrails under coaming

(4) Opening portholes with blinds on coaming

CHART TABLE TO PORT

Headroom: 6'4"

L-shaped chart table/desk, space for charts and

navigation instruments along the hull

(1) Adjustable swivel seat in vinyl leather, stainless steel legs

Electrical panel, access to charger and to electrical connection

Navigation instrument panels fitted in closed cubbyholes

Handhold, stainless steel handrails under coamings

(1) Stainless steel hand rail on bulkhead

(2) Opening portholes with blinds on coaming

White/red chart table light

PORT AFT HEAD

Headroom: 6'4"

Shower

Manual marine toilet w/21 gal. holding tank

Countertop with square synthetic resin sink

Storage cupboard with drawer, closed lockers

Toilet accessories: Paper dispenser, trash bin

(2) Mirrors

(2) Opening portholes with blinds on coaming

AFT CABINS

Headroom: 6'4"

Port cabin is slightly larger than starboard

(2) Cabins each with:

Double bed w/marine mattress

Fabric hanging closets on stainless steel rails

(1) Opening port with blind on coaming

(1) Opening porthole(s) with blind on cockpit

(1) Fixed hull port

ENGINE

Engine YANMAR Diesel 54 hp 4JH4AE w/Sail Drive

Engine control, key ignition, control panel in cockpit to starboard

Engine bed integrated in hull liner, soundproofed compartment w/insulating foam

(1) Alternator 12 Volt/80 Amp

(1) Rotomolded fuel tank, 53 gal (under starboard aft berth), w/gauge

Folding three-blade propeller

(1) Engine access through companionway, (2) engine access through aft cabins

ELECTRICAL

12 Volt circuit, 110 Volt circuit

(2) House batteries 110 Amp, (1) battery for engine 110 Amp, battery switch

(1) Charger 40 Amp, (1) shore power 110 Volt, battery isolator

Electrical panel backlit (12 Volt/110 Voly) (Circuit

breakers, ohmmeter 12 Volt/110 Volt ammeter, water gauge, fuel gauge, low battery, fuel and water alarm

(1) 12 Volt outlet, (7) 110 Volt outlets

Lighting: Salon halogen ceiling lights

Navigation, anchor, and deck lights

PLUMBING

(2) Rotomolded freshwater tanks (87 gal under forward berth, 63 gal under port aft berth)

Fresh water pressure system, accumulator tank, filter

Electric water heater 11gal. (110 Volt or engine heated)

Electrical shower drain pumps

(1) Electric bilge pump, (1) manual bilge pump

GAS

Storage for (1) propane tank in cockpit

OPTIONS

Consult your dealer for all available options